



## Specifications

### Description

Titan Compact 340L  
Split Heat Pump

### Model

340-17ASW-134

### Dimensions

2110 x 650mm  
660 x 635mm

### Hot Water

Production Rate L/hr  
(COP)

131 (3.74)

### Storage Size

340L

### Rated Delivery

315L

### Heat Output

6.22W

### Power Input

1.66kW

### COP of Heating

3.74

### Water Temp Setting

60°C

### Maximum Tank Temp Setting

70°C

### Compressor

39cc\*

### Refrigerant

R134a

### Electrical Supply

220-240V/50Hz/1Ph

### Circuit

15 Amps

### Water Connections

3/4" BSP - 20mm

### PTR Valve Setting

850kPa

### Expansion Ctrl Valve (ECV) Setting

700kPa

### PLV (without ECV fitted / with ECV fitted)

500kPa / 350 - 500kPa

### Operating Sound Level at 1.5M

58dBA

### Nett Weight (Empty)

180kg

### Ambient Air Operating Temperature

-10°C to +40°C

### Warranty

5 years (5 years tank, 2 years only electric and refrigeration)\*



Australian  
Standard

AS2712 LIC.2650  
SAI GLOBAL



WaterMark

AS3498 WMKA2531  
SAI GLOBAL

For more information call **1300 137 465** or visit [quantumenergy.com.au](http://quantumenergy.com.au)

\*Refer to [quantumenergy.com.au](http://quantumenergy.com.au) for warranty details or call 1800 644 705 | Under its policy of ongoing product development, Tasman Sinkware may from time to time change product specification without notice. All dimensions given are approximate and should be checked prior to installation.

### Hot water production rate

Ambient Temperature	Hot Water Production Rate (COP)
35°C	199LPH (5.30)
30°C	177LPH (4.69)
25°C	154LPH (4.09)
20°C	131LPH (3.57)
15°C	109LPH (3.03)
10°C	90LPH (2.53)
5°C	73LPH (2.09)
0°C	59LPH (1.71)
-5°C	51LPH (1.50)
-10°C	45LPH (1.34)

### Applications

Suitable for hotels, motels and resorts, apartment complexes, recreational facilities, and installable in Manifold for centralised system.



**8** People

### Federal Government ORER Zones and STC Value

Rebate's are available on application, please visit [quantumenergy.com.au](http://quantumenergy.com.au) for current rebate value and to find out your STC value.



ORER Zones	STC Value
Zone 1	23
Zone 2	22
Zone 3	27
Zone 4	28
Zone 5	28

For more information call **1300 137 465** or visit [quantumenergy.com.au](http://quantumenergy.com.au)

\*Refer to [quantumenergy.com.au](http://quantumenergy.com.au) for warranty details or call 1800 644 705 | Under its policy of ongoing product development, Tasman Sinkware may from time to time change product specification without notice. All dimensions given are approximate and should be checked prior to installation.